



**POWER REQUIRED:**  
 480 VAC, 3PH, 60 HZ  
 FUSED AT 30 AMPS

**AIR REQUIRED:**  
 5CFM @ 80 PSI

**SPEEDS:**  
 UP TO 120 PICKS PER MINUTE PER  
 ROBOT,  
 DEPENDING UPON WEIGHT,  
 HIGHER SPEEDS POSSIBLE,  
 CONSULT ENGINEERING

CASES AND PRODUCT CAN ENTER  
 FROM EITHER DIRECTION

CASE ELEVATION VARIES DEPENDING  
 ON HEIGHT OF CASE

TOLERANCE UNLESS NOTED		<b>FALLAS AUTOMATION</b>	
DECIMAL X.XX = ±0.010 X.XXX = ±0.005	PROJECT	SCALE	DRAWN BY <b>WG</b> DESIGNER <b>WG</b>
FRACTIONAL $\frac{X}{X} = \pm \frac{1}{32}$	TITLE <b>FLEXPICKER</b>		
ANGULAR ±0.5°	DATE <b>04/25/12</b>	DRAWING NUMBER <b>FP - FLEXPICKER</b>	SHEET NO. <b>1 of 1</b>
REV	REV DESCRIPTION		REV BY ECN